

## PRODUCT SELECTION MATRIX

# B2X™

## 18 HP



		B2X-18 Vehicle Mount Horizontal Drive				B2X-18 Vehicle Mount Vertical Drive				B2X-18 Portable			
		B2X-18H	B2X-18HT	B2X-18HX	B2X-18HXT	B2X-18V	B2X-18VT	B2X-18VX	B2X-18VXT	B2X-18P	B2X-18PTC	B2X-18PXC	B2X-18PETC
SPECIFICATIONS	Performance (standard NFPA Conditions)	Flow @ 50 PSI (3.4 BAR)	255 GPM (965 lpm)										
		Flow @ 100 PSI (6.9 BAR)	155 GPM (587 lpm)										
		Flow @ 150 PSI (10.3 BAR)	65 GPM (246 lpm)										
		Maximum Pressure	190 PSI (13.1 BAR)										
		Maximum Flow	300 GPM (1136 lpm)										
	Pump Type	2-Stage Centrifugal Pump											
	Pump Standard Connections	Intake	3" Female NPT/4" VIC Combination										
		Discharge	2-1/2" Female NPT/3" VIC Combination										
	Engine Type	B&S Vanguard											
	Engine Max Power	[Torque]	18 hp (13.4 KW) @ 4000 RPM [26.9 lb-ft (36.5 Nm) @ 2800 RPM]										
Drive	Orientation (timing belt, 1.88 : 1 speed increasing ratio)	Horizontal				Vertical				Vertical			
Frame		Base Mount with Industrial Isolators				Base Mount with Industrial Isolators				Carry Frame			
Dry Weight*		153 lbs (69 kg)	157 lbs (71 kg)	157 lbs (71 kg)	161 lbs (73 kg)	153 lbs (69 kg)	157 lbs (71 kg)	157 lbs (71 kg)	161 lbs (73 kg)	167 lbs (76 kg)	172 lbs (78 kg)	176 lbs (80 kg)	194 lbs (88 kg)

\* Approximated and varies based off option selections

		B2X-18H	B2X-18HT	B2X-18HX	B2X-18HXT	B2X-18V	B2X-18VT	B2X-18VX	B2X-18VXT	B2X-18P	B2X-18PTC	B2X-18PXC	B2X-18PETC	
OPTIONS	Primer	Guzzler Hand Primer	-	-	-	-	-	-	-	S	S	-	-	
		Remote Exhaust Primer w/Control Cable	-	-	S	S	-	-	S	S	-	-	-	-
		Exhaust Primer	-	-	-	-	-	-	-	-	-	-	S	-
		Electric Package - Electric Primer, LED work light, & Battery	-	-	-	-	-	-	-	-	-	-	-	S
	Muffler	Horizontal low tone	S	S	-	-	-	-	-	-	S	S	-	-
		Dual low tone	-	-	-	-	S	S	-	-	-	-	-	-
		Exhaust primer muffler	-	-	S	S	-	-	S	S	-	-	S	S
	Fuel Tank	Integral / 1.75 US gallons (6.6 L)	-	S	-	S	-	S	-	S	-	S	S	S
		Integral / 1 US gallon (3.8 L) w/ 3-way valve	-	-	-	-	-	-	-	-	-	-	-	-
	Controls	Engine Mount Control Panel	-	-	-	-	-	-	-	-	-	S	S	S
Remote Mount Control Panel - XCP Series		-	-	-	-	0	0	0	0	-	-	-	-	
Discharge Gauge	0-600 psi, 2-1/2" dial	-	-	-	-	-	-	-	-	S	S	S	S	
FastWire CTRL Cable	B&S 3' CTRL Cable with 8 pin connector (FWC-B-3)	S	S	S	S	S	S	S	S	-	-	-	-	
	Honda GX630 3' CTRL Cable with 8 pin connector (FWC-H-3)	-	-	-	-	-	-	-	-	-	-	-	-	

Standard        S  
Option            O  
Not Applicable —