

**PRODUCT SELECTION MATRIX**

# MARK-3<sup>®</sup>

## SERIES



|                |   |                           | MK-3               | MK-3D  | MK-3U            |                |
|----------------|---|---------------------------|--------------------|--|------------------|----------------|
| SPECIFICATIONS | Performance<br>(standard NFPA Conditions) | Flow @ 100 PSI (6.9 BAR)  |                    | 78 GPM (295 lpm)   |                  |                |
|                |   | Flow @ 150 PSI (10.3 BAR) |                    | 65 GPM (246 lpm)   |                  |                |
|                |   | Flow @ 200 PSI (13.8 BAR) |                    | 38 GPM (144 lpm)   |                  |                |
|                |   | Maximum Pressure          |                    | 380 PSI (26.2 BAR)   |                  |                |
|                |   | Maximum Flow              |                    | 98 GPM (371 lpm)   |                  |                |
|                | Engine Type                               | Air Cooled Gasoline       |                    | WATERAX 185cc  |                  |                |
|                | Engine Max Power                          | [Torque]                  |                    | "10 hp (7.5 kW) @ 5,500 rpm<br>[8.9 lb-ft (12 Nm) @ 5000 RPM]" |                  |                |
|                | Pump Type                                 | High Pressure             |                    | 4-Stage Centrifugal Pump                                       |                  |                |
|                | Pump Standard Connections                 | Intake                    |                    | 2" Male NPSH   | 2" Male NPSH     | 1-1/2" Male NH |
|                |   | Discharge                 |                    | 1-1/2" Male NPSH   | 1-1/2" Male NPSH | 1-1/2" Male NH |
| Fuel Connector |   |                           | Mercury            | Mercury  | SAE 45           |                |
| Frame          |   |                           | Backpackable Frame |  |                  |                |
| Dry Weight*    |   |                           | 58.3 lbs (26.4 kg) |  |                  |                |

\* Approximated and varies based off option selections

| OPTIONS | Decompression Switch       |                 | - | S | - |   |
|---------|----------------------------|-----------------|---|---|---|---|
|         | Fuel Tank                  | Air Transport   |   | 0 | 0 | - |
|         |                            | Metal Jerry Can |   | - | - | 0 |
|         | Suction Thread Protector   |                 | 0 | 0 | - |   |
|         | Discharge Thread Protector |                 | 0 | 0 | - |   |
|         | Discharge Gauge            |                 | 0 | 0 | 0 |   |
|         | Check Valve Monitor        |                 | 0 | 0 | 0 |   |
|         | Primer                     | Hand Primer     |   | 0 | 0 | 0 |

Standard      s  
Option        o  
Not Applicable —