

PRODUCT SELECTION MATRIX

STRIKER-2 SERIES



			STRIKER-2 Vehicle Mount	STRIKER-2 Portable
			STR2-13V STR2-13P	STR2-13P
SPECIFICATIONS	Performance (standard NFPA Conditions)	Flow @ 100 PSI (6.9 BAR)		97 GPM (367 lpm)
		Flow @ 150 PSI (10.3 BAR)		80 GPM (303 lpm)
		Flow @ 200 PSI (13.8 BAR)		58 GPM (202 lpm)
		Maximum Pressure		230 PSI (15.9 BAR)
		Maximum Flow		105 GPM (397 lpm)
	Pump Type	Air Cooled Gasoline		2-Stage Centrifugal Pump
	Pump Standard Connections	Intake		2" Male NPSH
		Discharge		1-1/2" Male NPSH
	Engine Type	Air Cooled Gasoline		Honda GX390
	Engine Max Power	[Torque]		11.7 hp (8.7 kW) @ 3,600 rpm [19.5 lb-ft (26.4 Nm) @ 2500 RPM]
Drive	Orientation (timing belt, 1.88 : 1 speed increasing ratio)		Mercury	Carry frame
Frame			Base Mount with Industrial Isolators	Mercury
Dry Weight*			127 lbs (58 Kg) 127 lbs (58 Kg)	Mercury

* Approximated and varies based off option selections

			STR2-13V STR2-13P	STR2-13P
OPTIONS	Muffler	Jabsco Hand Primer	-	s
	Fuel Tank	Honda	s	s
	Controls	1.6 US gallons (6.1 L)	s	s
	Discharge Gauge	Remote Mount Control Panels - XCP Series	o	-
	Check Valve Manifold	0-600 psi, 2-1/2" dial	-	s
	FastWire CTRL Cable	1-1/2" NPSH	-	s
	Primer	Honda 3' CTRL Cable with 8 pin connector (FWC-H1-3)	s	-

Standard s
Option o
Not Applicable —