

PRODUCT SELECTION MATRIX

SPECIFICATIONS	MINI CONTROL PANEL	
Enclosure	Steel, powder coated black	
Throttle Control	Vernier throttle with red emergency throttle idle push button	
Choke Control	Push/Pull engine choke cable	
Master	Toggle switch	
Engine Start	Push button	
Pressure Gauge	Dual unit 0-600 PSI/0-4000 kilopascals 2.5" dial	
Low Oil Alert	LED, red	
FastWire Control Cable	Quick-Connect 8-pin female industrial sealed connector	
Dimensions	8" W x 6-3/8" D x 6" H	
OPTIONS	MODEL	MCP
Low Pressure Protection	7 psi cutout switch w/ override	S
Weight		7.3 lbs



SPECIFICATIONS	PANEL MOUNT STANDARD CONTROL PANEL			
Enclosure	Black anodized aluminum			
Throttle Control	Vernier throttle with red emergency throttle idle push button			
Choke Control	Push/Pull engine choke cable			
Master	LED, Stainless steel toggle button			
Engine Start	Stainless steel push button			
Pressure Gauge	Compound -30 in Hg - 0 - 600 psi, 2.5" dial			
Low Oil Alert	Daylight visible LED, red			
FastWire Control Cable	Quick-Connect 8-pin female industrial sealed connector			
Dimensions	12-1/4" W x 3-1/4" D x 4-7/8" H			
OPTIONS	MODEL	PMSCP	PMSCP-LPP	PMSCP-DIESEL
Low Pressure Protection	7 psi cutout switch w/ override	—	S	S
Glow Plug Timer		—	—	S
High Water Temp. Warning Light	Daylight visible LED, red	—	—	S
Weight		5.5 lbs	6 lbs	6.5 lbs



SPECIFICATIONS	WATERAX CONTROL PANEL				
Enclosure	Stainless steel, closed, w/ protective handles				
Throttle Control	Vernier throttle with red emergency throttle idle push button				
Choke Control	Push/Pull engine choke cable				
Master	Toggle switch with flip switch protector				
Engine Start	Push button				
Pressure Gauge	Compound -30 in Hg - 0 - 600 psi, 4" dial				
Panel Light	Dual LED panel light				
Hour meter / Tachometer	SenDEC, LCD display				
Low Oil Alert	Daylight visible LED, red				
FastWire Control Cable	Quick-connect 8-pin female industrial sealed connector				
FastWire Power Cable	1' PWR CBL w/ Anderson connector				
Circuit protection	15A sealed circuit breaker				
Dimensions	12" W x 8" D x 13-5/8" H				
OPTIONS	MODEL	WCP	WCP-F	WCP-W	WCP-FW
Low Pressure Protection	7 psi cutout switch w/ override	S	S	S	S
Work Light	Light w/Toggle Switch	0	0	0	0
Electric Primer	Electric Primer w/Momentary Switch	0	0	0	0
Water Level Monitor	IC, 14 LED display, 180 deg. Visibility	—	—	S	S
Foam Level Monitor	IC, 14 LED display, 180 deg. visibility, Class A	—	S	—	S
Weight		24.5 lbs	25.2 lbs	25.2 lbs	25.9 lbs



Standard s
 Option o
 Not Applicable -