



PRODUCT SELECTION MATRIX

BB-4[®]

18 HP



		BB-4-18 Vehicle Mount Horizontal Drive				BB-4-18 Vehicle Mount Vertical Drive				BB-4-18 Portable				
		BB-4-18H	BB-4-18HT	BB-4-18HX	BB-4-18HXT	BB-4-18V	BB-4-18VT	BB-4-18VX	BB-4-18VXT	BB-4-18P	BB-4-18PTC	BB-4-18PXTC	BB-4-18PETC	
SPECIFICATIONS	Performance (standard NFPA Conditions)	Flow @ 150 PSI (10.3 BAR)									100 GPM (379 lpm)			
		Flow @ 250 PSI (17.2 BAR)									83 GPM (303 lpm)			
		Flow @ 350 PSI (24.1 BAR)									50 GPM (189 lpm)			
		Maximum Pressure									440 PSI (30.3 BAR)			
		Maximum Flow									106 GPM (401 lpm)			
	Pump Type	High Pressure - Medium Flow								4-Stage Centrifugal Pump				
	Pump Standard Connections	Intake									2" Male NPSH			
		Discharge									1-1/2" Male NPSH			
	Engine Type	Air Cooled Gasoline								B&S Vanguard				
	Engine Max Power	[Torque]	18 hp (13.4 KW) @ 4000 RPM [26.9 lb-ft (36.5 Nm) @ 2800 RPM]											
Frame		Base Mount with Industrial Isolators				Base Mount with Industrial Isolators				Carry Frame				
Drive	Orientation (timing belt, 1.88 : 1 speed increasing ratio)	Horizontal				Vertical				Vertical				
Dry Weight*		153 lbs (69 kg)	157 lbs (71 kg)	157 lbs (71 kg)	161 lbs (73 kg)	153 lbs (69 kg)	157 lbs (71 kg)	157 lbs (71 kg)	161 lbs (73 kg)	167 lbs (76 kg)	172 lbs (78 kg)	176 lbs (80 kg)	194 lbs (88 kg)	

* Approximated and varies based off option selections

		BB-4-18H	BB-4-18HT	BB-4-18HX	BB-4-18HXT	BB-4-18V	BB-4-18VT	BB-4-18VX	BB-4-18VXT	BB-4-18P	BB-4-18PTC	BB-4-18PXTC	BB-4-18PETC	
OPTIONS	Primer	Guzzler Hand Primer	-	-	-	-	-	-	-	S	S	-	-	
		Remote Exhaust Primer w/Control Cable	-	-	S	S	-	-	S	S	-	-	-	
		Exhaust Primer	-	-	-	-	-	-	-	-	-	S	-	
		Electric Package - Electric Primer, LED work light, & Battery	-	-	-	-	-	-	-	-	-	-	-	S
	Muffler	Horizontal low tone	S	S	-	-	-	-	-	-	-	-	-	-
		Dual low tone	-	-	-	-	S	S	-	-	S	S	-	-
		Exhaust primer muffler	-	-	S	S	-	-	S	S	-	-	S	S
	Fuel Tank	Integral / 1.75 Us gallons (6.6 L)	-	S	-	S	-	S	-	S	-	S	S	S
		Integral / 1 Us gallon (3.8 L) w/ 3-way valve	-	-	-	-	-	-	-	-	-	-	-	-
	Controls	Engine Mount Control Panel	-	-	-	-	-	-	-	-	-	S	S	S
Remote Mount Control Panel - XCP series		0	0	0	0	0	0	0	0	-	-	-	-	
Discharge Gauge	0-600 psi, 2-1/2" dial	-	-	-	-	-	-	-	-	S	S	S	S	
FastWire CTRL Cable	B&S 3' CTRL Cable with 8 pin connector (FWC-B-3)	S	S	S	S	S	S	S	S	-	-	-	-	
	Honda GX630 3' CTRL Cable with 8 pin connector (FWC-H-3)	-	-	-	-	-	-	-	-	-	-	-	-	

Standard s
Option o
Not Applicable —